

|->

Title 22@ Social Security

|->

Division 4.5@ Environmental Health Standards for the Management of Hazardous Waste

|->

Chapter 14@ Standards for Owners and Operators of Hazardous Waste Transfer, Treatment, Storage, and Disposal Facilities

|->

Article 14@ Landfills

|->

Section 66264.302@ Action Leakage Rate

66264.302 Action Leakage Rate

(a)

The Department shall approve an action leakage rate for landfill units subject to section 66264.301(c) or (d). The action leakage rate is the maximum design flow rate that the leak detection system (LDS) can remove without the fluid pressure head on the bottom liner exceeding 1 foot (30.5 cm) at any given portion of the liner. The action leakage rate shall include an adequate safety margin to allow for uncertainties in the design (e.g., slope, hydraulic conductivity, thickness of drainage material), construction, operation, and location of the LDS, waste and leachate characteristics, likelihood and amounts of other sources of liquids in the LDS, and proposed response actions (e.g., the action leakage rate shall consider decreases in the flow capacity of the system over time resulting from siltation and clogging, rib layover and creep of synthetic components of the system, overburden pressures, etc.).

(b)

To determine if the action leakage rate has been exceeded, the owner or operator shall convert the weekly or monthly flow rate from the monitoring data obtained under section 66264.303(c) to an average daily flow rate (gallons per acre per day) for each sump. Unless the Department approves a different calculation, the average daily flow rate for each sump shall be calculated weekly during the active life and closure period, and monthly during the post-closure care period when

monthly monitoring is required under section 66264.303(c).