```
California Code Of Regulations
|->
Title 22@ Social Security
|->
Division 4.5@ Environmental Health Standards for the Management of Hazardous Waste
|->
Chapter 15@ Interim Status Standards for Owners and Operators of Hazardous Waste Transfer, Treatment, Storage, and Disposal Facilities
|->
Article 11@ Surface Impoundments
|->
Section 66265.229@ Special Requirements for Ignitable or Reactive Waste
```

66265.229 Special Requirements for Ignitable or Reactive Waste

Ignitable or reactive waste shall not be placed in a surface impoundment unless the waste and the impoundment satisfy all applicable requirements of chapter 18 of this division, and:

(a)

the waste is treated, rendered, or mixed before or immediately after placement in the impoundment so that: (1) the resulting waste, mixture, or dissolution of material no longer meets the definition of ignitable or reactive waste under sections 66261.21 or 66261.23 of this chapter; and (2) section 66265.17(b) is complied with; or

(1)

the resulting waste, mixture, or dissolution of material no longer meets the definition of ignitable or reactive waste under sections 66261.21 or 66261.23 of this chapter; and

(2)

section 66265.17(b) is complied with; or

(b)

(1) the waste is managed in such a way that it is protected from any material or conditions which may cause it to ignite or react; and (2) the owner or operator obtains a certification from a qualified chemist or engineer, registered in California

that to the best of the chemist's or engineer's knowledge and opinion, the design features or operating plans of the facility will prevent ignition or reaction; and (3) the certification and the basis for it are maintained at the facility; or

(1)

the waste is managed in such a way that it is protected from any material or conditions which may cause it to ignite or react; and

(2)

the owner or operator obtains a certification from a qualified chemist or engineer, registered in California that to the best of the chemist's or engineer's knowledge and opinion, the design features or operating plans of the facility will prevent ignition or reaction; and

(3)

the certification and the basis for it are maintained at the facility; or

(c)

the surface impoundment is used solely for emergencies.