

66265.253 Containment

If leachate or run-off from a pile is a hazardous waste, then either:

(a)

(1) the pile shall be placed on an impermeable base that is compatible with the waste under the conditions of treatment or storage; (2) the owner or operator shall design, construct, operate, and maintain a run-on control system capable of preventing flow onto the active portion of the pile during peak discharge from at least a 25-year storm; (3) the owner or operator shall design, construct, operate, and maintain a run-off management system to collect and control at least the water volume resulting from a 24-hour, 25-year storm; and (4) collection and holding facilities (e.g., tanks or basins) associated with run-on and run-off control systems shall be emptied or otherwise managed expeditiously to maintain design capacity of the system; or

(1)

the pile shall be placed on an impermeable base that is compatible with the waste under the conditions of treatment or storage;

(2)

the owner or operator shall design, construct, operate, and maintain a run-on control system capable of preventing flow onto the active portion of the pile during peak discharge from at least a 25-year storm;

(3)

the owner or operator shall design, construct, operate, and maintain a run-off management system to collect and control at least the water volume resulting from a 24-hour, 25-year storm; and

(4)

collection and holding facilities (e.g., tanks or basins) associated with run-on and run-off control systems shall be emptied or otherwise managed expeditiously to maintain design capacity of the system; or

(b)

(1) the pile shall be protected from precipitation and run-on by some other means; and (2) no liquids or wastes containing free liquids shall be placed in the pile.

(1)

the pile shall be protected from precipitation and run-on by some other means; and

(2)

no liquids or wastes containing free liquids shall be placed in the pile.