## 66265.254 Design and Operating Requirements

## (a)

Section 66265.254@ Design and Operating Requirements

The owner or operator of each new waste pile handling RCRA hazardous waste on which construction commences after January 29, 1992, each lateral expansion of a waste pile unit on which construction commences after July 29, 1992, and each such replacement of an existing waste pile unit that is to commence reuse after July 29, 1992 shall install two or more liners and a leachate collection and removal system above and between such liners, and operate the leachate collection and removal systems, in accordance with section 66264.251(c), unless exempted under section 66264.251 (l), (m), or (n), of this chapter; and shall comply with the procedures of section 66265.221(b). "Construction commences" is as defined in section 66260.10 of this chapter under "existing facility".

## (b)

The owner or operator of each new waste pile handling only non-RCRA hazardous waste on which construction commences after February 18, 1996, each lateral expansion of a waste pile unit on which construction commences after February 18, 1996, and each such replacement of an existing waste pile unit that is to commence reuse after February 18, 1996 shall install two or more liners and a leachate collection and removal system above and between such liners, and operate the leachate collection and removal systems, in accordance with section 66264.251(c), unless exempted under section 66264.251 (l), (m) or (n) of this

chapter; and shall comply with the procedures of section 66265.221(b).

"Construction commences" is as defined in section 66260.10 of this chapter under "existing facility".