

|->

Title 22@ Social Security

|->

Division 4.5@ Environmental Health Standards for the Management of Hazardous Waste

|->

Chapter 15@ Interim Status Standards for Owners and Operators of Hazardous Waste Transfer, Treatment, Storage, and Disposal Facilities

|->

Article 12@ Waste Piles

|->

Section 66265.255@ Action Leakage Rates

66265.255 Action Leakage Rates

(a)

The owner or operator of waste pile units subject to section 66265.254 shall submit a proposed action leakage rate to the Department when submitting the notice required under section 66265.254. The Department will establish an action leakage rate, either as proposed by the owner or operator or modified using the criteria in this section.

(b)

The Department shall approve an action leakage rate for waste pile units subject to section 66265.254. The action leakage rate is the maximum design flow rate that the leak detection system (LDS) can remove without the fluid pressure head on the bottom liner exceeding 1 foot (30.5 cm) at any govern portion of the liner. The action leakage rate shall include an adequate safety margin to allow for uncertainties in the design (e.g., slope, construction, operation, and location of the LDS, waste and leachate characteristics, likelihood and amounts of other sources of liquids in the LDS, and proposed response actions (e.g., the action leakage rate shall consider decreases in the flow capacity of the system over time resulting from siltation and clogging, rib layover and creep of synthetic components of the system, overburden pressures, etc.).

(c)

To determine if the action leakage rate has been exceeded, the owner or operator

shall convert the weekly flow rate from the monitoring data obtained under section 66265.260, to an average daily flow rate (gallons per acre per day) for each sump. Unless the Department approves a different calculation, the average daily flow rate for each sump shall be calculated weekly during the active life and closure period.