

|-&gt;

Title 22@ Social Security

|-&gt;

Division 4.5@ Environmental Health Standards for the Management of Hazardous Waste

|-&gt;

Chapter 15@ Interim Status Standards for Owners and Operators of Hazardous Waste Transfer, Treatment, Storage, and Disposal Facilities

|-&gt;

Article 28@ Air Emissions Standards for Equipment Leaks

|-&gt;

Section 66265.1054@ Standards: Pressure Relief Devices in Gas/Vapor Service

## **66265.1054 Standards: Pressure Relief Devices in Gas/Vapor Service**

### **(a)**

Except during pressure releases, each pressure relief device in gas/vapor service shall be operated with no detectable emissions, as indicated by an instrument reading of less than 500 ppm above background, as measured by the method specified in Section 66265.1063(c).

### **(b)**

(1) After each pressure release, the pressure relief device shall be returned to a condition of no detectable emissions, as indicated by an instrument reading of less than 500 ppm above background, as soon as practicable, but no later than 24 hours after each pressure release, except as provided in Section 66265.1059. (2) No later than 24 hours after the pressure release, the pressure relief device shall be monitored to confirm the condition of no detectable emissions, as indicated by an instrument reading of less than 500 ppm above background, as measured by the method specified in Section 66265.1063(c).

### **(1)**

After each pressure release, the pressure relief device shall be returned to a condition of no detectable emissions, as indicated by an instrument reading of less than 500 ppm above background, as soon as practicable, but no later than 24 hours after each pressure release, except as provided in Section 66265.1059.

**(2)**

No later than 24 hours after the pressure release, the pressure relief device shall be monitored to confirm the condition of no detectable emissions, as indicated by an instrument reading of less than 500 ppm above background, as measured by the method specified in Section 66265.1063(c).

**(c)**

Any pressure relief device that is equipped with a closed-vent system capable of capturing and transporting leakage from the pressure relief device to a control device as described in Section 66265.1060 is exempt from the requirements of subsections (a) and (b) of this section.