

|-&gt;

Title 22@ Social Security

|-&gt;

Division 4.5@ Environmental Health Standards for the Management of Hazardous Waste

|-&gt;

Chapter 42@ Requirements for Management of Fluorescent Light Ballasts Which Contain Polychlorinated Biphenyls (PCBs)

|-&gt;

Section 67428.1@ Transportation Requirements

## **67428.1 Transportation Requirements**

### **(a)**

A transporter of twelve or fewer non-leaking fluorescent light ballasts which contain PCBs shall be exempt from Chapter 13 of this division provided that the containers which contain the ballasts do not include any other hazardous waste.

### **(b)**

A transporter of more than twelve non-leaking light ballasts which contain PCBs shall be exempt from Article 1 and Article 2 of Chapter 13 of this division pertaining to the transportation of a hazardous waste provided all of the following conditions are met: (1) The transporter shall use a shipping paper which contains all the information required pursuant to Title 49, Code of Federal Regulations, Part 172, Subpart C to document the transportation of the fluorescent light ballasts. The shipping paper must accompany the shipments of fluorescent light ballasts. (2) The total amount of fluorescent light ballasts which contain PCBs being transported is no more than two 55 gallon drums of non-leaking fluorescent light ballasts per load. (3) The containers used for transportation of fluorescent light ballasts which contain PCBs meet all applicable federal and state regulations. (4) When transporting hazardous waste consisting of fluorescent light ballasts which contain PCBs, the containers which contain the ballasts shall not include any other hazardous waste. (5) Any discharges or spills of hazardous waste consisting of fluorescent light ballasts which contain PCBs shall be reported and cleaned up as required in Article

3, Chapter 13 of this division. (6) The transporter of light ballasts shall retain for three years a legible copy of each manifest or shipping documents to document the transportation of hazardous waste consisting of fluorescent light ballasts which contain PCBs.

**(1)**

The transporter shall use a shipping paper which contains all the information required pursuant to Title 49, Code of Federal Regulations, Part 172, Subpart C to document the transportation of the fluorescent light ballasts. The shipping paper must accompany the shipments of fluorescent light ballasts.

**(2)**

The total amount of fluorescent light ballasts which contain PCBs being transported is no more than two 55 gallon drums of non-leaking fluorescent light ballasts per load.

**(3)**

The containers used for transportation of fluorescent light ballasts which contain PCBs meet all applicable federal and state regulations.

**(4)**

When transporting hazardous waste consisting of fluorescent light ballasts which contain PCBs, the containers which contain the ballasts shall not include any other hazardous waste.

**(5)**

Any discharges or spills of hazardous waste consisting of fluorescent light ballasts which contain PCBs shall be reported and cleaned up as required in Article 3, Chapter 13 of this division.

**(6)**

The transporter of light ballasts shall retain for three years a legible copy of each manifest or shipping documents to document the transportation of hazardous waste

consisting of fluorescent light ballasts which contain PCBs.

**(c)**

Transfer of hazardous waste consisting of fluorescent light ballasts which contain PCBs from one container to another container is not subject to the requirements of this division provided the containers hold no other hazardous waste.